



parallel speaker cable
2 x 0.75 - 6.0 mm² - zip cord - PVC
 • cable with separable conductor pair
 • for banana plug speaker connections
 • for screw-type speaker connectors

PVC

Parallel loudspeaker cables suit very well in installations. Easily dividable conductors can be attached to connectors or screw type terminals at cabinets or amplifiers very quickly. The HiFi market often uses this parallel cable with its transparent PVC jacket because of the high number of strands and low resistance values.

construction

conductor **stranded bare copper**
 outer jacket **PVC**

electric

insulation resistance **20 MΩ x km**
 max. operating voltage **50/75 V AC/DC**

mechanics

working temperature
 installed **-30°C / +70°C**
 moved **-10°C / +70°C**

order code	cond. cross section mm ²	cond. construction mm	conductor resistance Ω/km	dimensions mm	cable color	weight kg/m	standard lengths m
LYP007S	0.75	24 x 0.20	26	2.35 x 4.9	black	0.02	15 / 30 / 50 / 100 / 500
LYP007T	0.75	24 x 0.20	26	2.35 x 4.9	transparent	0.02	15 / 30 / 50 / 100 / 500
LYP007W	0.75	24 x 0.20	26	2.35 x 4.9	white	0.02	15 / 30 / 50 / 100 / 500
LYP015S	1.5	48 x 0.2	13.3	2.8 x 5.8	black	0.04	15 / 30 / 50 / 100 / 500
LYP015T	1.5	48 x 0.2	13.3	2.8 x 5.8	transparent	0.04	15 / 30 / 50 / 100 / 500
LYP015W	1.5	48 x 0.2	13.3	2.8 x 5.8	white	0.04	15 / 30 / 50 / 100 / 500
LYP025S	2.5	78 x 0.2	7.98	3.6 x 7.4	black	0.06	15 / 30 / 50 / 100 / 500
LYP025T	2.5	78 x 0.2	7.98	3.6 x 7.4	transparent	0.06	15 / 30 / 50 / 100 / 500
LYP025W	2.5	78 x 0.2	7.98	3.6 x 7.4	white	0.06	15 / 30 / 50 / 100 / 500
LYP060T	6.0	189 x 0.2	3.3	6.1 x 12.5	transparent	0.14	15 / 30 / 50 / 100

technical specifications are subject to change