

**AES/ EBU digital wiring cable****2 x 0.14 mm<sup>2</sup> - PVC**

- 0.14 mm<sup>2</sup> conductor cross section (AWG 26)
- 110 Ohm characteristic impedance
- AL/PET foil shield
- just 3.2 mm outer diameter

**PVC**

This versatile cable can be used for a range of applications thanks to its low outer diameter of 3.2 mm and option of two different outer jacket types. The version with PVC outer jacket can be used as cabling for 19 racks, stage boxes and DMX systems; however, the OTW203 is also available with a halogen-free and flame-retardant FRNC outer jacket for installations. In both these areas, the OTW203 transmits digital - and naturally also analogue - signals as efficiently as control signals for DMX and other systems.

**construction**

cond. construction	tinned copper braid, 7 x 0.16 mm
cond. cross section	0.14 mm <sup>2</sup>
insulation	Foam-Skin PE
shielding	stranded tinned copper drain wire + AL/PET foil
outer jacket	PVC
overall diameter	3.2 mm

**mechanics**

min. bending radius	20 mm
working temperature	-20°C / +70°C

**electric**

conductor resistance	< 135 Ω/km
capacitance	
cond./cond.	44 pF/m
characteristic impedance	110 Ω
attenuation [dB/100m]	
1 MHz	3.3
3 MHz	5.3
10 MHz	8.4
insulation resistance	> 10 GΩ x km
test voltage	
cond./cond.	1200 V
cond./shield	500 V

order code	outer jacket	outer Ø mm	cable color	weight kg/m	standard lengths m
OTW203Y	PVC	3.2	black	0.01	50 / 100 / 200 / 500

technical specifications are subject to change