



FRNC

Eca

StarQuad pro audio cable**4 x 0.22 mm² - FRNC**

- 0.22 mm² conductor cross section (AWG 24)
- quad connection: 2 x 0.44 mm² (AWG 21)
- AL/PET foil shield (100% coverage)
- flame retardant and non corrosive (FRNC)
- CPR class Eca acc. to EN50575
- ¹ quad connection: two diagonally opposite conductors are attached to one conductor
- ² each pair from two diagonally opposite conductors forms one transmission path

The SQ422H is ideal for installations. The jacket is of flame-retardant halogen-free FRNC while the four finely stranded wires are protected from electromagnetic interference with an AL foil shield and 100% screening earthed with a drain wire. Like all star-quad cables, the four cores are wired in such a way that opposite cores are electrically connected, thus reducing the cable's susceptibility to electromagnetic interference - as does the extremely short lay length of the core twisting.

construction

cond. construction	stranded tinned copper, 28 x 0.10 mm
cond. cross section	0.22 mm ²
insulation	polyethylene (PE)
core arrangement	4 cores twisted to a star quad
shielding	AL/PETP foil
drain wire	stranded tinned copper, 7 x 0.20 mm
overall diameter	5.6 mm

mechanics

min. bending radius	40 mm
working temperature	-30°C / +70°C
halogen-free	acc. to IEC 60754-1-1
flame retardancy	acc. to IEC 60332-1-2
heat of combustion	202 kWh/km

electric

conductor resistance	77 Ω/km
insulation resistance	> 30 GΩ x km
capacitance	
cond./cond. ¹	125 pF/m
cond./shield ¹	180 pF/m
cond./cond. ²	50 pF/m
cond./shield ²	100 pF/m

order code	cable color	weight kg/m	standard lengths m
SQ422H	black	0.04	30 / 50 / 100 / 200 / 300

technical specifications are subject to change