



**professional microphone cable**  
**2 x 0.22 mm<sup>2</sup> - extra heavy sheath - PVC**

- 0.22 mm<sup>2</sup> conductor cross section (AWG 24)
- ultra-low capacitance 60 pF/m (18 pF/ft)
- bare copper spiral shield
- extra heavy overall sheath

## PVC

The MC 2000 can handle the toughest requirements of live performance and is an excellent choice for the rental sector. It features all the outstanding characteristics of the MY206 - 0.22 m<sup>2</sup> conductor cross-section, spiral shield, superb flexibility, precise twisting to avoid electromagnetic interference - plus an extra-thick PVC outer jacket to give a total diameter of 6.5 mm. The MC 2000 is supremely flexible, allowing for easy drum winding and unwinding, and lies smoothly and flat for stage use. The cable is ideal for workshop production of custom cables.

### design

cond. construction	stranded bare copper, 28 x 0.10 mm
cond. cross section	0.22 mm <sup>2</sup>
insulation	polyethylene (PE)
core arrangement	2 cores + twisted cotton tracers
shielding	bare copper spiral shield
outer jacket	PVC, matt
overall diameter	6.5 mm

### mechanics

min. bending radius	30 mm
working temperature	-20°C / +70°C

### electric

conductor resistance	< 85 Ω/km
capacitance	
cond./cond.	60 pF/m
cond./shield	110 pF/m
insulation resistance	> 0.1 GΩ x km

order code	cable color	weight kg/m	standard lengths m
MC2000SW	black	0.05	30 / 50 / 100 / 200 / 300 / 500

technical specifications are subject to change