



**triaxial camera cable**  
flexible, Ø 8.4 mm - PUR

- flexible silver-plated stranded inner conductor
- robust PUR overall jacket
- max. transmission length 500-720 m (depending on camera type)

**PUR** **UHD** **4K**

Triaxial cables are primarily used for electrical connections for video cameras and transmission systems. Their high-quality materials and high-precision balanced design maximise their transmission properties (low attenuation, even characteristic impedance). The smooth outer braided screen enables cameras to be supplied with power.

**construction**

inner conductor	stranded silver-plated copper, 7 x 0.36 mm
insulation	foam PE, Ø 4.5 mm
1. shield	silver-plated copper braid, >90% coverage
insulation	TPE
2. shield	bare copper braid, 85% coverage
outer jacket	PUR
overall diameter	8.4 mm

**mechanics**

min. bending radius	60 mm
---------------------	-------

**electric**

characteristic impedance	75 Ω ± 2%
capacitance cond.	
1. shield	54 pF/m
DC resistance	
inner conductor	< 26 Ω/km
1. shield	< 10 Ω/km
screening attenuation	
30 MHz - 1 GHz	> 75 dB
attenuation [dB/100m]	
1 MHz	0.8
5 MHz	1.8
10 MHz	2.6
20 MHz	3.7
50 MHz	6.9
100 MHz	8.8
return loss	
1 - 100 MHz	> 26 dB
100 - 300 MHz	> 23 dB
max. operating voltage	500 V

order code	ref. type	outer jacket	working temperature	cable color	weight kg/m	standard lengths m
TRIA08LP	triax 8	PUR	-40°C / +70°C	red	0.1	50 / 100 / 200 / 300 / 500

technical specifications are subject to change